

Technical Data Sheet

GLEIVO Beeswax No. 315

Suitable for	Interior timber such as panelling and furniture that has been pre-treated with LIVOS oils or stains. Also suitable for the regular maintenance of linoleum. To refresh waxed timber, cork and stone surfaces. Not suitable for areas exposed to water splashes.
Technical Qualities	Liquid. Applicable by airless spraying. Produces a satin glossy finish when completely dry.
Full declaration	Isoaliphates, beeswax, micronized wax, carnauba wax, linseed oil, orange oil, alumina, rosemary oil.
Color	Clear. Coloration is possible by adding a max. 10% of VINDO Natural Gloss Paint No. 629
Dilution	Ready to use.
Application method	Apply a very thin coat by brushing, spraying or with a wadded cloth at temperatures above 12 °C.
Coverage	For Initial treatment: 1 liter is sufficient for approximately 25 m ² i.e. 40 ml/m ² ; could be considerably less, depending on the condition and absorbency of the surface. Always do a test application! For surface maintenance: 1 liter is sufficient for an average of 100 m ² i.e. 10 ml/m ² .
Drying time	At 23° C and 50% relative humidity, approximately 2 - 4 hours.
Cleaning	Clean equipment immediately after use with SVALOS Thinner No. 222.
Specific gravity	0.78 g/ml.
Safety advice	Contains limonene. S 2 Keep out of the reach of children. S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label
Disposal	According to locally regulated laws.
Container sizes	0.05 lt; 0.25 lt; 1 lt; 2.5 lt.
Storage	Cool and dry. Close lid tightly after use.
Packaging	Made of polyethylene (PE). This material is ground water neutral and recyclable. See reverse for application instructions.

Preparation

The surface must be dry, solid, clean, and free of grease and dust. Pre-treatment with LIVOS oils, e.g. MELDOS Natural Resin Hardening Oil No. 264, ARDVOS Universal Wood Oil No. 266 or KALDET Transparent Wood Stain No.270.

To ensure compatibility of surfaces previously treated with products from another manufacturer, do a test application on an inconspicuous area.

Before use, shake or stir the product well.

Application

Apply GLEIVO Beeswax No. 315 very thinly and evenly with a brush or cloth. After approximately 2 - 4 hours, polish (by wood in the direction of the wood grain) with a wadded cloth, a wax brush or a floor polisher with a white non abrasive pad.

Cleaning

Remove dust with a vacuum cleaner or mop.

Rubber abrasion and stubborn dirt can be removed with SVALOS Thinner No. 222. Clean with TRENA pH-Neutral Cleaner No. 556 according to demand.

Care

According to usage and location, apply an after-treatment with GLEIVO Beeswax No. 315 once or twice a year.

Important tips

Ensure good ventilation during application and drying times.

Too thick application needs intensive mechanical polishing. Strong electrostatic charge e.g. of a synthetic paint etc. will be reduced or eliminated by a very thin coating of the beeswax.

On surfaces coated with DELVA Smooth Render No. 426, GLEIVO No. 315 protects against abrasion and dirt. GLEIVO delays the possible fading of the DELVA admixed plant pigments / mixtures and imparts a brilliant, satin gloss.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

December 2010 Rev. 2.4