

Rubiomonocoat SOAP SATIN STRIPPER

PRODUCT DESCRIPTION:

Stripper, non-foaming, easily removes Rubio Monocoat Soap Satin. Suitable both for machine and manual use.

APPLICATION:

- Dilute with preferably lukewarm water to a ratio of 5 to 10 %, depending on the amount of coats of RMC Soap Satin previously applied.
- Apply to the floor and allow to work for 10 -15 min.
- Remove the dissolved residue with a rubber squeegee or a water-vacuum.
- Do not allow the solution to dry on the floor.
- Thoroughly mop up with water in order to completely neutralise all traces of the RMC Soap Satin Stripper.
- For stubborn stains: use 10 to 20% RMC Soap Satin Stripper.

Note: After this treatment, it is strongly recommended to treat with RMC Maintenance Oil.

PRECAUTIONS:

The product is irritating.
Store out of reach of children.
Avoid contact with eyes and skin.
Wear suitable gloves and optional eye protection.
Do not allow to freeze.

TECHNICAL CHARACTERISTICS:

pH: +/- 13
S.G.: +/- 1,04
Colour: colourless to light yellow
Smell: distinct

PACKAGE:

1 and 5 litre can.

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.
Date TDS: 30/08/10.

MUYLLE  **FACON**

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiomonocoat.com

