

Rubiomonocoat HIGH TRAFFIC PROTECTION

DESCRIPTION:

Rubio Monocoat High Traffic Protection offers extra protection for parquet floors in heavy traffic areas. The first cleaning – with undiluted product – can already be carried out 36 hours after treatment with **Rubio Monocoat Oil Plus**. Surfaces treated with **Rubio Monocoat Oil Plus** can be cleaned weekly with a solution of 250 ml **Rubio Monocoat High Traffic Protection** per bucket of water (10 liter).

INSTRUCTIONS:

Preparation: Eliminate dirt and dust from the floor.

First treatment: Apply the product without diluting it and in a single layer, preferably with the special Rubio Monocoat brush, or alternatively with a string mop or a cloth mop. or a soft satin finish: apply one coat only. Respect a 90 minute drying period.

For a high gloss finish: apply a second coat. Leave the floor to dry for 60 minutes between applications. After a final drying time of 90 minutes, the parquet is ready to be treaded on.

COVERAGE:

Coverage for the undiluted product: 1 liter/20 m².

These usages are merely indicative. It is always recommended to make a sample in order to calculate the exact usage.

Weekly and monthly maintenance:

Mix 250 ml **Rubio Monocoat High Traffic Protection** in 10 liters of water. The maintenance can either be carried out manually (eg. with a Swiffer) or with an industrial cleaner (up to 1000 rotations per minute). The floor can be walked on again 30 minutes after treatment.

GENERAL INFORMATION:

The drying times indicated only apply to well ventilated areas.

To the **reduce** the gloss finish of the **RMC High Traffic Protection**: use water and **RMC Soap** in a ratio of 1/1.

To remove **RMC High Traffic Protection**: use water and **RMC Soap Satin Stripper** in a ratio of 1/4.

TECHNICAL CHARACTERISTICS:

Water based soap polish

pH: +/- 8

Unit weight: +/- 1,03

Colour: white

Odour: specific

STORAGE:

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging. Do not allow to freeze.

PACKAGING:

1 and 5 L cans.

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.
Date TDS: 24/06/10.

MUYLLE FACON

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.

Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)

Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823

info@muyllefacon.be - www.rubiomonocoat.com

