

# Rubiomonocoat OIL PLUS

## HARDWAX OIL PROTECTS AND COLOURS YOUR WOOD IN ONE SINGLE LAYER.



### SPECIFIC FEATURES:

Rubio Monocoat Oil Plus colours and protects your wood in one single layer. Unlike the traditional hardwax oils, **Rubio Monocoat Oil Plus** will connect with the wood ply by means of a molecular reaction, as a result of which a durable protection is obtained. This molecular connection enables the **Rubio Monocoat Oil Plus** to embed in the surface's upper microns immediately. The wood fibres can only combine with a certain amount of oil. Oil, which has not reacted, doesn't bed and needs to be removed.

### RENOVATION:

Where scratches or burn marks are present, or where heavy wear is showing (either in patches or large areas of the floor) a renovation treatment with **Rubio Monocoat Oil Plus** is recommended. Local repair is easy: only the wood fibres, which have come free through damage, will combine with new oil. It also applies if a completely new colour is desired over the entire surface area of a previously treated floor. Please consult our instructions sheet on renovation.

### DRYING TIME:

Provided that the room is well-ventilated, the surface is walkable after 24 to 36 hours.

Areas with very heavy traffic should preferably be protected for +/- one week, with a porous material, 48 hours after the application of **Rubio Monocoat Oil Plus**.

### MAINTENANCE:

After treatment with **Rubio Monocoat Oil Plus**, the floor requires 3 weeks to harden completely. During the first week, it is advisable to only clean with a vacuum cleaner or a dust mop fitted with a dry cloth. Do NOT use damp cloths! During the second week, a damp cloth, soaked in clean water and wrung out thoroughly, can be used with due care. After 3 weeks, the floor can be maintained using maintenance products from the **Rubio Monocoat** range. Consult our maintenance manual.

### SAFETY:

**Rubio Monocoat Oil Plus** is 100% environmentally friendly. Consult our safety sheet for these specifications.

### TRANSPORT:

There are no specific measures to be taken for transport by road, sea or air.

### INSTRUCTIONS:

Consult our application manual for full instructions.

### CONSUMPTION:

1 liter / 30 to 50 m<sup>2</sup>.

Consult the safety sheet before use.

### MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.

Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)  
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823  
info@muyllfacon.be - [www.rubiomonocoat.com](http://www.rubiomonocoat.com)

- 100 % VOC-FREE!
- Respects the natural 'look and feel' of the wood
- Low consumption - 1 liter for 30 to 50 m<sup>2</sup>
- No starting marks or overlaps
- 35 standard colours
- Easy to maintain
- Doesn't contain water
- Applies to all kinds of wood, on furniture and floors (solid wood, veneer wood, MDF, etc...)
- Durable protection, highly resistant to wear
- Water-resistant: (suited for application in kitchens, bathrooms)
- Resistant to heat until 100 °C

### TECHNICAL SPECIFICATIONS:

Basis: mixture of natural oils and hardwax.

Colour: 35 standard colours.

Consistency: liquid

Flash point: cc (astm d93): > 102°C (Pensky Martens)

Fixed dust percentage: > 90%

Density: Pure: 0.93 g/cm<sup>3</sup> - colours: from 1 to 1.4 g/cm<sup>3</sup>

VOC: 0 g/l (2004/42/CE, 1999/13/CE)

Resistance to water (NEN-EN 13442): no visual or tangible changes.

Resistance to wear: (NEN 2072 – Taber Abraser en CS 17 sanding wheels): strong absorption basantol liquid, only after 800 to 1000 rotations.

Resistance to heat until 100 °C

### STORAGE:

The product can be stored up to 24 months. Store in dry conditions and in the original packaging.

### PACKAGING:

0,20 ml - 100 ml - 0,5 liter - 1 liter - 2,5 liter - 5 liter - can.

### PRECAUTION:

The product may NOT be diluted!  
Cloths, saturated with oil, may spontaneously combust.  
After usage, they need to be soaked in water before disposal.

PROVIDED BY:

These guidelines are the result of tests and our own experience and are provided in good faith. Since we have no control over individual circumstances, we cannot be held responsible for any damage incurred as a result of incorrect or inappropriate use of said guidelines.

