

# Rubiomonocoat PRECOLOR BLACK

## CREATIVE ZONE

### PRODUCT DESCRIPTION:

**Rubio Monocoat Precolor Black** was specially developed to create contrast effects in combination with the products in the **Rubio Monocoat** range. The best possible molecular binding between the **RMC Oil** and the wood remains guaranteed.

### CHARACTERISTICS:

- Colours the wood in one layer.
- Can be treated afterwards with an oil or varnish from the **Rubio Monocoat** range.
- Doesn't scratch up the wood fibres.

### APPLICATION:

#### Mechanical

- Sand or smooth the grain of the planks to be treated until they are satisfactorily finished.
- Remove all dust from the planks.
- Apply **Rubio Monocoat Precolor Black** with a roller or spray.
- Spread the products evenly with brushes.
- Dry the planks in a drying tunnel.
- Apply a **Rubio Monocoat** product or some other finish.

#### Manual

- Sand or smooth the grain of the planks to be treated until they are satisfactorily finished.
- Remove all dust from the surface of the planks.
- Apply **Rubio Monocoat Precolor Black** with a brush or cloth in the lengthwise direction of the planks. Treat 2 or 3 planks at the same time.
- Rub over evenly with a cloth until there are no overlaps visible.
- Wait until the **Rubio Monocoat Precolor Black** is dry. If a light colour is desired, the surface should dry for 24 to 36 hours, depending on the temperature and ventilation in the room.
- Apply a **Rubio Monocoat** product or some other finish.

### CONSUMPTION:

Depending on the sort of wood and the preparation: about 20 to 50 g/m<sup>2</sup>.

### TECHNICAL CHARACTERISTICS:

Physical State (20°C) : Liquid

Form/Colour : black .

Odour : Sweet.

Flash point (CC) : 58 °C

Density (20°C) : 0,94 kg/l

Solubility in water : Complete solubility.

Soluble in : Alcohol, ethers .

### STORAGE:

When can is properly closed, at least 12 months' shelf life, if stored dry and frost-free.

### PACKAGING:

1-litre and 5-litre can.

PROVIDED BY:

These guidelines are the result of tests and our own experience and are provided in good faith. Since we have no control over individual circumstances, we cannot be held responsible for any damage incurred as a result of incorrect or inappropriate use of said guidelines.

Consult the safety sheet before use.

**MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.**

Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)  
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823  
info@muyllefacon.be - [www.rubiomonocoat.com](http://www.rubiomonocoat.com)

